

## DESCRIPTION

FY.51260US1NP

PATENT

### ENGINE CONTROL SYSTEM, VEHICLE HAVING THE SAME, METHOD FOR CALCULATING FUEL CENTER OF GRAVITY, AND METHOD FOR CONTROLLING ENGINE

Technical Field

[0001]

#### CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application is a U.S. National Phase application of International Application No. PCT/JP2005/001378, filed February 1, 2005, which is based upon and claims priority to Japanese Patent Application No. 2004-025547, filed February 2, 2004 each of which is hereby incorporated by reference in its entirety.

#### BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present invention relates to an engine control system, a vehicle having the same, a method for calculating the fuel center of gravity of an engine, and a method for controlling an engine.

Background Art

[0002]

Description of the Related Art

[0003] A well-known method for optimizing the ignition timing of spark ignition internal combustion engines is a method of determining ignition timing on the basis of negative ion current in the cylinder (e.g., refer to Patent Document 1 JP-A-6-33855). In the method disclosed in Patent Document 1, negative ion current flowing in the cylinder directly after ignition is measured, and the time from the ignition at which the value of the negative ion current becomes the maximum is determined. Then the time difference between the determined time and minimum spark advance for best torque (MBT) is calculated, and the calculated time difference is added to or subtracted from the preceding ignition timing to thereby determine the present ignition timing.

Patent Document 1: JP-A-6-33855

## DISCLOSURE SUMMARY OF THE INVENTION

### [0004] ~~Problems to be Solved by the Invention~~

[0003]

The ~~Thus~~, conventional ignition timing control using negative ion current is based on the following ~~assumption~~ assumptions:

(1) The ~~peak position of the~~ maximum negative ion current after ignition has ~~correlation~~ correlates with combustion pressure.

(2) The peak of combustion pressure is at 15° after top dead center ~~during operation at which ignition timing agrees with~~ when the engine operates with an MBT (i.e., Maximum Best Timing for torque) ignition timing.

(3) Therefore, adjusting the ignition timing so that the ~~peak position of the~~ maximum negative ion current ~~comes~~ is adjusted to 15° after top dead center ~~enables~~ correlates the ignition timing ~~to agree with~~ MBT.

[0005] ~~However, the peak position of the~~ maximum combustion pressure actually depends upon ~~on the~~ operating ~~state~~ conditions of the engine. ~~Item Assumption (2) is therefore is not always true~~ an assumption that holds only in a limited operating region. Specifically, for example, at MBT during which combustion speed is low, the ion current peak position does ~~not come to occur~~ at 15° after top dead center. ~~Accordingly~~ Thus, the conventional control does not adequately function over ~~could not make the ignition timing agree with MBT in a wide operating region.~~

[0006] ~~The invention has been made in view of the problems of the conventional method.~~ Accordingly, it is an object of one embodiment of the present invention to provide a system or method capable of ~~control such as making controlling~~ ignition timing to better agree with MBT timing over a wide range of operating conditions to thereby increase fuel efficiency, reduce exhaust gas, and/or improve drivability without measuring torque and combustion pressure.

[0007] One aspect of an embodiment of the present invention relates to ~~Means for Solving the Problems~~

Aan engine control system arranged and configured in accordance with certain features, aspects and advantages of the present according to the invention includes ~~comprises~~ :

an ion current measuring unit that ~~measures~~ is adapted to measure the negative ion current in a combustion chamber of an engine. The system also comprises ; a crank-angle measuring unit that ~~measures~~ is adapted to measure an engine crank angle. The system also comprises ; and a controller that is adapted to controls the engine on the basis of a first crank angle at which the ~~an~~ increase rate of ~~the~~ the negative ion current ~~are~~ relative to ~~gainst~~ the crank angle ~~becomes more than~~ exceeds a first specified value and a second crank angle at which the increase rate becomes a second specified value after ~~becoming~~ exceeding the first specified value.

[0008] Another aspect of an embodiment of the present invention relates to a method for calculating ~~the~~ a fuel center of gravity of an engine. The method comprises according to the invention includes the steps of: measuring the a negative ion current in a combustion chamber of the engine; determining a first crank angle at which the ~~an~~ increase rate of the negative ion current ~~against~~ relative to the engine crank angle ~~becomes more than~~ exceeds a first specified value; determining a second crank angle at which the increase rate becomes a second specified angle value after ~~becoming~~ exceeding the first specified angle; and calculating the fuel center of gravity from the first crank angle and the second crank angle.

[0009] A further aspect of the present invention relates to a method for controlling the operation of an engine. The method ~~according to the invention~~ includes the steps of: measuring the a negative ion current in a combustion chamber of the engine; determining a first crank angle at which the increase rate of the negative ion current ~~against~~ relative to an engine crank angle ~~becomes more than~~ exceeds a first specified value; determining a second crank angle at which the increase rate becomes a second specified angle value after ~~becoming~~ exceeding the first specified angle; and controlling the engine on the basis of the first crank angle and the second crank angle.

[0010] Another aspect of the present invention relates to configurations in which the first specified value defines a [0009]

~~According to the invention, an engine is controlled or the fuel center of gravity is calculated on the basis of the rising point and~~ the second specified value defines a ~~the~~ peak point of the negative ion current on a negative ion current characteristic curve. Thus, as

distinct from the control or calculation based only on the peak point of negative ion current, ~~correct control is improved or calculation can be achieved~~ even when the peak point shifts as the operating state changes. Accordingly, ~~the ability to adjust the control of making the ignition timing agree with to approximate MBT is improved can be achieved in over~~ a wide operating region without necessarily measuring torque and combustion pressure.

#### Advantages of the Invention

[0010]

~~Thus, the invention enables ignition timing to be agreed with MBT in a wide operating state such as at low combustion speed, thus increasing fuel efficiency, reducing exhaust gas, or improving drivability.~~

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0011] These and other features, aspects and advantages of the present invention will now be described with reference to the drawings of a preferred embodiment, which embodiment is intended to illustrate and not to limit the invention. The figures comprise nine drawings.

[0012] ~~[Fig. 1]~~ Fig. 1 is a side view of a motorcycle according to an embodiment.

[0013] ~~[Fig. 2]~~ Fig. 2 is a schematic diagram of an engine.

[0014] ~~[Fig. 3]~~ Fig. 3 is a characteristic diagram of negative ion current and combustion pressure plotted against crank angles.

[0015] ~~[Fig. 4]~~ Fig. 4 shows two different characteristic curves of negative ion current plotted against crank angles.

[0016] ~~[Fig. 5]~~ Fig. 5(a) shows characteristic curves for heat rate and combustion mass ratio while; Fig. 5(b) shows a characteristic curve for negative ion current.

[0017] ~~[Fig. 6]~~ Fig. 6 is a graph showing the relationship between engine speed and ignition timing, and fuel center of gravity and so on.

[0018] ~~[Fig. 7]~~ Fig. 7 is a graph showing the relationship between ignition timing and torque, fuel center of gravity and so on.

[0019] ~~[Fig. 8]~~ Fig. 8 is a graph showing the relationship between ignition timing and torque, fuel center of gravity and so on.

## Description of Reference Numerals and Signs

[0012]

1: engine

5: combustion chamber

14: ignition plug (ion current measuring unit)

16: engine control unit (controller)

19: crank angle sensor (crank angle measuring unit)

100: motorcycle (vehicle)

B: first crank angle

C: second crank angle

G: third crank angle

## Best Mode for Carrying Out the Invention

[0013]

### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0020] An embodiment that is arranged and configured in accordance with certain features, aspects and advantages of the invention will be described with reference to the drawings.

[0021] Referring to Fig. 1, a vehicle according to the embodiment is a vehicle ~~having comprising~~ an engine 1, specifically, a motorcycle 100, which is a kind of saddle-type vehicle. The motorcycle 100 ~~has comprises~~ a body 101, a front wheel 102, and a rear wheel 103. The body 101 ~~has comprises~~ an air intake port 104, an air cleaner 105, the engine 1, and a muffler 106. The air intake port 104 and the air cleaner 105 can be connected ~~to each other~~ via an intake duct 107. The air cleaner 105 and the engine 1 ~~are can be~~ connected together via an intake pipe 108. The engine 1 and the muffler 106 ~~are can be~~ connected via an exhaust pipe 109.

[0022] The engine 1 preferably is a spark-ignition internal combustion engine, which is, in this embodiment, ~~of~~ a water-cooled four-cycle multiple cylinder type. Alternatively, the engine 1 ~~may can be~~ of an air-cooled type. The number of cylinders of the engine 1 is not limited but may be, for example, one in certain embodiments.

[0023] Referring to Fig. 2, the engine 1 ~~includes comprises~~ a crankcase 2, a cylinder block 3 ~~fixed onto connected to~~ the crankcase 2, a cylinder head 4 fixed onto the

cylinder block 3, and a head cover (not shown) ~~fixed onto~~ connected to the cylinder head 4. The cylinder block 3 ~~has~~ comprises a cylinder bore 3a therein, in which a piston 6 is disposed. The piston 6 connects to a connecting rod 7. The connecting rod 7 connects to a crankshaft 8 disposed in the crankcase 2.

[0024] The cylinder head 4 ~~has~~ comprises a recess 4a on the surface adjacent to the cylinder block 3. The recess 4a, the piston 6, and the cylinder bore 3a define a combustion chamber 5. The cylinder head 4 ~~has~~ comprises an intake valve opening 4b and an exhaust valve opening 4c which are open to the recess 4a. The cylinder head 4 also ~~has~~ comprises an intake valve 9 and an exhaust valve 10 for opening and closing the intake valve opening 4b and the exhaust valve opening 4c, respectively.

[0025] The intake valve 9 and the exhaust valve 10 ~~are~~ can be opened or closed by an intake camshaft 11 and an exhaust camshaft 12, respectively. The intake camshaft 11 and the exhaust camshaft 12 preferably connect to a variable valve timing mechanism 13. The variable valve timing mechanism 13 receives a valve-timing control signal *a* from an engine control unit (hereinafter, referred to as an ECU) 16 to control the open-close timing of the intake valve 9 and the exhaust valve 10 by the intake camshaft 11 and the exhaust camshaft 12, respectively.

[0026] An ignition plug 14 ~~is~~ can be placed in the cylinder head 4. The ignition plug 14 ~~is~~ can be disposed substantially at the center of the recess 4a. The electrode of the ignition plug 14 ~~is~~ can be exposed to the inner surface of the recess 4a. The ignition plug 14 preferably connects to an igniter 15. The igniter 15 receives an ignition-timing control signal *b* from the ECU 16 to control the spark generation timing of the ignition plug 14.

[0027] In ~~this one~~ presently preferred embodiment, the ignition plug 14 advantageously ~~is used also as~~ comprises a negative ion current probe. The ignition plug 14 connects to a positive electrode 17a of a ~~battery~~ battery 17. A negative electrode 17b of the ~~battery~~ battery 17 preferably connects to the cylinder head 4 via a wattmeter 18 for grounding. Thus, the ignition plug 14 ~~is always generally~~ is positively charged. ~~Obviously~~ In some embodiments, the negative ion current probe may be provided separately.

[0028] The engine 1 ~~includes~~ preferably comprises a crank-angle sensor 19 and a knock sensor 20 for detecting knocking. Detection signals from the crank-angle sensor 19

and the knock sensor 20 ~~are~~ can be input to the ECU 16. As will be described later, when ~~the~~ occurrence of knocking is detected by the knock sensor 20, the ignition timing control by the ECU 16 ~~is~~ can be adjusted to reduce or eliminate the knocking ~~restricted~~.

[0029] The negative ion current generated in the combustion chamber 5 varies as ~~the~~ combustion progresses. Specifically, when the ignition plug 14 ignites the air fuel mixture in the combustion chamber 5, a first chemical action is activated. The first chemical reaction causes, ~~so that~~ electrons in atoms or molecules to collide with one another, which ~~to~~ generates energy. The atoms or molecules thus ~~come~~ become into an excited, which causes sufficient state ~~accompanied by~~ heat generation ~~suffieient~~ to shift to an energy state higher than a normal stable state. ~~With the shifting to~~ In the excited state, chemical light emissions ~~around in~~ ultraviolet ray spectrums occurs, which results in an ~~to~~ increase in positive ions. As a result, the negative ion current in the combustion chamber 5 increases. The negative ion current is collected by the ignition plug 14 (i.e., that is used also as an ~~the~~ negative ion-current probe) and the ~~detection value of~~ detected by the wattmeter 18 is input into the ECU 16.

[0030] Fig. 3 shows characteristic curves of negative ion current E and combustion pressure P plotted against crank angles. As shown in Fig. 3, the characteristic of the negative ion current E exhibits almost the same tendency as that of the combustion pressure P. In other words, the negative ion current E peaks as substantially the same crank angle as the combustion pressure P peaks. The negative ion current E can therefore be used as information indicative of changes in combustion pressure P, flame area, or heat generation.

[0031] However, the crank angle at which the combustion pressure P becomes the maximum depends on the operating state of the engine 1. Accordingly, the peak position of the negative ion current E depends on the operating state of the engine 1 (refer to Fig. 4, which is merely a conceptual diagram for explanation, and is not based on actual measurement data). Therefore, the control based only on the peak position of the characteristic curve of the negative ion current E cannot flexibly cope with changes in engine load, so that it cannot be applied to a wide variety of operating state.

[0032] However, the inventor has realized the following points. Specifically speaking, as has been described, even when the ignition timing is at MBT, the characteristic

curve of the negative ion current  $E$  varies as the operating state of the engine 1 varies (refer to curves  $E1$  and  $E2$  of Fig. 4), so that the crank angle corresponding to the peak position of the characteristic curve changes. However, crank angles that change little even if the operating state changes can be calculated from a plurality of crank angles corresponding to a plurality of points on the characteristic curve, such as crank angles corresponding to a fuel center of gravity. In other words, some intersections between a set crank angle and the characteristic curve are generally consistent with respect to the detected negative ion current. Point  $P0$  in Fig. 4 indicates ~~than intersectione~~ point corresponding to such a crank angle. Controlling based on this crank angle enables flexible response to fluctuations in load, allowing control applicable to wide operating regions without necessarily measuring torque and combustion pressure.

**[0033]** A specific example of the control will be described hereinbelow. An Operation control that can be used to adjust for adjusting ignition timing to MBT will first be described.

**[0034]** Fig. 5(b) shows ~~changes~~ a variation of the negative ion current  $E$  plotted against crank angles; Fig. 5(a) shows ~~variations~~ ~~changes of in~~ heat rate  $D$  and combustion mass ratio  $F$  also plotted against crank angles. Referring to Fig. 5(b), symbol  $A$  indicates a crank angle for an ignition point; symbol  $B$  indicates a crank angle for any rising point of the ion current on the ion-current curve (hereinafter, referred to as a first crank angle); and symbol  $C$  indicates a crank angle for any peak point of the ion current (hereinafter, referred to as a second crank angle).

**[0035]** As can be inferred from the graphical presentation shown in Fig. 5(a) and Fig.(b), the increase of at the rising point crank angle, the ion current ~~increase changes for the~~ crank angle at the rising point becomes from less than a specified value (hereinafter, referred to as a first specified value) to an ion current increase value that is more than that firste specified value. In other words, the slope of the line  $E$  in Fig. 5(b) increases from the first value to a value more than the first value. On the other hand, a At the peak of the ion current, the ion current increase falls from the first specified value or more a value higher than the first specified value to a second specified value (hereinafter, referred to as a second specified value, which may be different from or equal to the first specified value) or less a value lower



than the second specified value. In other words, at the peak of the ion current, the slope of the line E decreases from a value equal to or greater than the first specified value to a value equal to or less than a second specified value. —Accordingly, the point at which the increase rate becomes the first specified value or a value higher than the first specified value ~~more~~ can be referred to as a rising point, and the point at which the increase rate becomes the first specified value and then falls ~~becomes~~ the second specified value or less ~~a value less than the second specified value~~ can be referred to as a peak point. The method for determining the rising point and the peak point is not limited at all. For determining the rising point and the peak point, there is no need to calculate the actual increase; for example, the rising point and the peak point can be determined by comparing the values of the ion current and a predetermined threshold.

[0036] In the ~~illustrated~~ embodiment, the first crank angle B is set to a crank angle corresponding to the rising point of the ion current curve, and the second crank angle C is set to a crank angle generally corresponding to the peak point of the ion current curve. The first crank angle B and the second crank angle C, however, may not exactly agree with the rising point and the peak point, respectively, but may be slightly off the rising point and the peak point because of measurement error or disturbance. In short, the first crank angle B and the second crank angle C ~~may have only to be~~ substantially regarded as the rising point and the peak point, respectively.

[0037] As shown in Figs. 5(a) and 5(b), the negative ion current generating point (the position corresponding to the first crank angle B) generally correlates with ~~to be regarded as the beginning of combustion. This point preferably is the point follows an~~ that ignition delay time, ~~which follows has passed after~~ the discharge of the ignition plug 14, and this point preferably is the point at which heat generation begins by the start of the initial combustion. The peak point thereafter (the position corresponding to the second crank angle C) preferably is substantially the point of maximum ~~at which the heat generation during combustion becomes the maximum.~~ Accordingly, substantially the midpoint thereof is generally estimated to correspond to the fuel center of gravity.

[0038] The substantially middle point between the first crank angle B and the second crank angle C can therefore be regarded as a crank angle (hereinafter, referred to as a

third crank angle) G, which ~~generally corresponds~~ corresponding to the fuel center of gravity. Thus, the fuel center of gravity can be calculated from the first crank angle B and the second crank angle C. As will be described later, when the ignition timing is at MBT, the fuel center of gravity does not vary greatly even if the load varies. Accordingly, in this embodiment, the ECU 16 presets the crank angle corresponding to the fuel center of gravity at MBT as a target crank angle, and controls the ignition timing of the igniter 15 so that the third crank angle determined by measuring the negative ion current agrees with the target crank angle.

[0039] When the ignition timing is at MBT, the fuel center of gravity does not vary greatly by load fluctuations. Accordingly, the target crank angle may be set without much not to be varied variation caused by engine load. In some embodiments, ~~tacceding to the load conditions of the engine 1~~. The target crank angle may be a fixed value. On the other hand, the target crank angle may depend on the operating characteristics of the individual difference or secular changes of the engine 1, or may be appropriately varied on the basis of an operational expression (e.g., function or mathematical equation) or a table containing parameters.

[0040] Fig. 6 shows the relationship between engine speed and ignition timing, fuel center of gravity, and so on. As discussed above, tThe fuel center of gravity preferably is calculated from the first crank angle B and the second crank angle C. Referring to Fig. 6, the first crank angle B, the second crank angle C, and the third crank angle G indicate "ignition angle", "the end of combustion", and "the fuel center of gravity", respectively. The interval between A and B indicates an ignition delay period, and the interval between B and C indicates a combustion period. In this embodiment, the target crank angle corresponding to the fuel center of gravity preferably is set at about 1-5° before top dead center. The ignition timing is feed-back controlled so that the third crank angle G becomes the target crank angle (1-5° before the top dead center). Depending upon the application, there may be some variation in the target crank angle.

[0041] Fig. 7 shows the relationship between ignition timing and torques and fuel center of gravity, and so on. As shown in Fig. 7, the torque depends on ignition timing, and becomes the maximum when the ignition timing is at MBT. On the other hand, as the ignition timing advances to the top dead center, the fuel center of gravity shifts from the

position of after top dead center to the position of before top dead center. The torque therefore increases as the fuel center of gravity moves from the position of after top dead center to the position of before top dead center, and becomes the maximum when the fuel center of gravity is about at 2-3° before the top dead center, and in turn decreases as the fuel center of gravity moves toward the before top dead center.

[0042] The graph shows that when the ignition timing is controlled so that the third crank angle G (a crank angle corresponding to the fuel center of gravity) becomes about 2-3° before top dead center, the ignition timing becomes about 35-36° before top dead center, so that the ignition timing generally agrees with MBT.

[0043] As has been described, by the control according to the embodiment, the target value of the third crank angle G does not vary significantly ~~by the fluctuation of~~ due to variations in the operating state. Accordingly, in the case of complicatedly varying of the lift amount and the open-close timing of the intake valve 9, or in the case of simply varying the engine load conditions such as engine rotation speed and throttle opening, the ignition timing can easily ~~be agreed~~ be brought into general alignment with MBT by the above-described control using the measurement of the negative ion current in the combustion chamber 5.

[0044] An experiment by the inventor shows that, for example, for MBT at a specific operating state x of a specific internal combustion engine, the first crank angle B at which a negative ion current at the beginning of combustion ~~starts to generate~~ was occurs at about 11° before top dead center, and the second crank angle C at which the negative ion current peaks ~~becomes to the peak thereafter~~ was occurs at about 9° after top dead center. The difference between the second crank angle C and the first crank angle B was about 20°, and the third crank angle G in the center thereof was about 10° ~~delayed behind~~ after the first crank angle B, or about 1° before top dead center.

[0045] Then, for the internal combustion engine, the third crank angle G was measured under different load conditions. Specifically, the load conditions were changed by changing the throttle opening or rotation speed. The measurement of the third crank angle (the angle in the middle between the first crank angle B and the second crank angle C) G shows that, although the rising point and the peak point of the negative ion current curve varies, the third crank angle G is always about 1° before top dead center under any load

condition. Briefly, with the internal combustion engine, the third crank angle G at which the ignition timing is at MBT was substantially the same at all load conditions. For example, the comparison between Figs. 7 and 8 indicating torque characteristic etc. under different load conditions shows that the third crank angles G at which the ignition timing generally agrees with MBT are both about  $1^\circ$  before top dead center.

[0046] Under the same conditions of bore/stroke ratio and connecting rod ratio ( $\lambda$ ), the combustion speed changes as the rotation speed and load of the engine 1 change, so that the first crank angle B and the second crank angle C determined from the negative ion current changes. However, the third crank angle G corresponding to the fuel center of gravity is held substantially constant at MBT.

[0047] Conventionally, heat generation has been estimated from pseudo combustion mass ratio converted from combustion pressure. According to the estimation, about 30% of the entire heat generation distribution at MBT has been estimated to be located before top dead center, while the remaining 70% has been estimated to be located after top dead center, and the fuel center of gravity has been estimated to be located after top dead center.

[0048] However, by the method for calculating fuel center of gravity according to the embodiment, the fuel center of gravity is in the vicinity of top dead center, or more specifically,  $1\text{--}5^\circ$  before top dead center. The difference may be by the following reasons: most of negative ions during combustion generate at the excitation of cool flame and blue flame. However, the heat generation determined from combustion pressure is the result of light emission of amplitude transition, such as flaming reaction after cool flame and blue flame, or solid-state radiation around infrared rays. Accordingly, the conventional method takes little thought of the excitation, so that the fuel center of gravity determined from combustion pressure may be delayed behind the fuel center of gravity based on the negative ion current as in the embodiment.

[0049] The control method according to ~~the one~~ embodiment of the present invention is a method of controlling the engine 1 by measuring a negative ion current, which is unpaired electrons, during true combustion, and controlling the engine 1 on the basis of the negative ion current, not by estimating an instantaneous value of the thermal conductivity of

combustion gas from combustion pressure as in the past. Thus, the embodiment can reduce errors in calculating the fuel center of gravity, thus increasing control accuracy. Also, the embodiment can facilitate control of the engine 1 without a dedicated sensor in the combustion chamber 5.

**[0050]** While the control according to the embodiment is such that ignition timing is adjusted to MBT so as to obtain a maximum torque, ~~the invention is not limited to that other configurations are possible.~~

For example, in an operating state in which knocking may occur, knocking can be reduced or prevented by disabling the control or by setting the target value of the third crank angle G later than the target value of the embodiment (a target value for MBT). It is also possible to reduce or prevent knocking ~~in a manner by~~ detecting knocking with the knock sensor 20, and disabling the control according to the detection result or by setting the target value of the third crank angle G to ~~the~~ a delayed position.

**[0051]** The fuel center of gravity by the negative ion current varies significantly at flame off due to exhaust gas recirculation (EGR) in which exhaust gas is recirculated in intake gas, a lean-burn air-fuel ratio state, or a stratified-charge combustion state. Thus, it is also possible to control the EGR rate and air-fuel ratio on the basis of the fluctuations of the fuel center of gravity per unit time to prevent flame off. In short, the control according to the invention may ~~be achieved to~~ also be used to reduce or prevent the flame off of the engine 1.

**[0052]** For EGR (since the structure for EGR is well known, a description thereof will be omitted), it is possible to calculate a third crank angle corresponding to the fuel center of gravity by the above-described method, and calculate the fluctuation of the third crank angle, and to control the EGR rate such that the EGR rate is decreased with increases in the sensed fluctuations ~~so as to decrease with increasing fluctuation~~. This enables control of the EGR rate without a specific sensor and can reduce or prevent flame off of the engine 1.

**[0053]** It is also possible to calculate a third crank angle corresponding to the fuel center of gravity by the above-described method, and calculate the fluctuation of the third crank angle, and to control the open-close timing of the intake valve 9 and the exhaust valve 10 of the engine 1 so that the overlap period of the intake valve 9 and the exhaust valve 10

decreases with increasing fluctuation. This enables control of valve timing without a specific sensor and can prevent flame off of the engine 1.

[0054] Thus, ~~a~~According to the one embodiment, ignition timing can be agreed with correlated to MBT under a variety of operating states, including decreased combustion speed, thereby improving fuel efficiency, decreasing exhaust gas, and increasing drivability. Also, with a variable valve timing mechanism that ~~complicatedly and variably~~ controls the lift amount and open-close timing of an intake valve or when engine load conditions, such as rotation speed and throttle opening, are simply varied, for example, the ignition timing can easily be ~~agreed~~ adjusted to with MBT, allowing an optimum or preferable combustion state to be achieved. Also, controlling ignition timing so that fuel center of gravity is delayed behind MBT can reduce or eliminate ~~prevent~~ knocking and reduce the generation of NOx components ~~of in the~~ exhaust gas components.

[0055] The calculation of the fuel center of gravity and operation control according to the embodiment are based on the characteristic of negative ion current for a crank angle sensed by the crank-angle sensor 19. However, the "crank angle" of the invention is nothing but a parameter indicative of the process of combustion; parameters that may be technical equivalents or proxies ~~see~~ to the crank angle can also be regarded as the "crank angle". This is because such parameters have generally one-to-one correspondence with the crank angle. Accordingly, for example, it is also possible to specify the rising point of negative ion current on the basis of the actual crank angle, while ~~to specify~~ specifying the peak point on the basis of another parameter (e.g., elapsed time) other than the actual crank angle.

[0056] Although the operation control system for the engine 1 according to the illustrated embodiment is mounted to the motorcycle 100, the engine control system ~~according to the invention~~ is not necessarily mounted to vehicles. For example, the operation control system may be mounted to engine testing units, performance evaluation units, or applicable tools/ ~~TCertain features, aspects and advantages of the present invention is have~~ advantagesous to in vehicular application, for example, in vehicles such as motorcycles and in the control of the engines of such the vehicles. Moreover, although the present invention has been described in terms of a certain embodiment, other embodiments apparent to those of

ordinary skill in the art also are within the scope of this invention. Thus, various changes and modifications may be made without departing from the spirit and scope of the invention. For instance, various components may be repositioned as desired. Moreover, not all of the features, aspects and advantages are necessarily required to practice the present invention. Accordingly, the scope of the present invention is intended to be defined only by the claims that follow.

CLAIMS WHAT IS CLAIMED IS:

1. An engine control system comprising:
  - an ion current measuring unit ~~that~~ adapted to measures ~~the~~ a negative ion current in a combustion chamber of an engine;
  - a crank-angle measuring unit ~~that measures~~ adapted to measure an engine crank angle; and
  - a controller ~~that~~ adapted to controls the engine on the basis of a first crank angle at which ~~the~~ an increase rate of the negative ion current ~~against~~ relative to the crank angle becomes more than a first specified value and a second crank angle at which the increase rate becomes a second specified value after becoming the first specified value.
2. The engine control system according to Claim 1, wherein
  - the first crank angle is a crank angle corresponding to ~~the~~ a rising point of the negative ion current on a negative ion current curve indicative of variations in negative ion current ~~against~~ relative to crank angles; and
  - the second crank angle is a crank angle corresponding to ~~the~~ a peak point of the negative ion current on the negative ion current curve.
3. The engine control system according to Claim 2, wherein the controller is adapted to calculates from the first crank angle and the second crank angle a third crank angle corresponding to ~~the~~ a fuel center of gravity ~~from the first crank angle and the second crank angle~~, and the controller is adapted to control ~~controls the engine~~ an engine ignition timing so that the third crank angle ~~reaches~~ approximates a specified target crank angle.
4. The engine control system according to Claim 3, wherein the specified target crank angle is ~~set so as not to be~~ not changed according to engine load conditions.
5. The engine control system according to Claim 3, wherein the ~~crank angle is set to a specified crank angle~~ corresponds ing to MBT.
6. The engine control system according to Claim 3, wherein the specified target crank angle is set to a specified predetermined crank angle delayed behind MBT.
7. The engine control system according to Claim 2, wherein the controller is adapted to calculates ~~the~~ a variation rate of the third crank angle corresponding to the fuel



center of gravity from the first crank angle and the second crank angle, and the controller is adapted to controls the an exhaust gas recirculation (EGR) rate of the engine so that the engine-EGR rate decreases when the with increasing variation rate increases.

8. The engine control system according to Claim 2, wherein the controller is adapted to calculates the a variation rate of the third crank angle corresponding to the fuel center of gravity from the first crank angle and the second crank angle, and the controller is adapted to controls the an open-close timing of an intake valve and an exhaust valve of the engine so that the overlap period of the intake valve and the exhaust valve decreases with as the variation rate increases increasing variation rate.

9. The engine control system according to Claim 1 in combination with a vehicle comprising an engine and the engine control system according to one of Claims 1 to 8.

10. A method for calculating the a fuel center of gravity of an engine, the method comprising the steps of:

measuring the a negative ion current in a combustion chamber of the engine;  
determining a first crank angle at which the an increase rate of the negative ion current against relative to an the engine crank angle becomes more than exceeds a first specified value;

determining a second crank angle at which the increase rate becomes a second specified angle after becoming exceeding the first specified valueangle; and

calculating the fuel center of gravity from the first crank angle and the second crank angle.

11. A method for controlling the operation of an engine, the method comprising the steps of:

measuring the a negative ion current in a combustion chamber of the engine;  
determining a first crank angle at which the an increase rate of the negative ion current against relative to an engine crank angle becomes more than exceeds a first specified value;

determining a second crank angle at which the increase rate becomes a second specified angle after becoming exceeding the first specified anglevalue; and

controlling the engine on the basis of the first crank angle and the second crank angle.

12. The method for controlling the operation of an engine according to Claim 11, wherein

the step of controlling the engine comprises the steps of:

calculating a third crank angle corresponding to the fuel center of gravity from the first crank angle and the second crank angle; and

controlling engine ignition timing so that the third crank angle ~~becomes~~ approximates a specified target crank angle.

**ABSTRACTENGINE CONTROL SYSTEM, VEHICLE HAVING THE SAME,  
METHOD FOR CALCULATING FUEL CENTER OF GRAVITY, AND METHOD  
FOR CONTROLLING ENGINE**

**ABSTRACT OF THE DISCLOSURE**

An engine control system ~~It is an object of the present invention to enables~~ engine control to ~~make cause~~ ignition timing agree with ~~to approximate~~ MBT without ~~necessarily~~ measuring torque and combustion pressure. The negative ion current in an engine combustion chamber is measured; and a first crank angle B corresponding to a first rate in change of the negative ion current curve E is identified. ~~the rising point on the characteristic curve of a negative ion current E and a~~ A second crank angle C corresponding to a second rate in change of the negative ion current curve E also is identified. ~~the peak point on the characteristic curve are determined; and t~~The ignition timing is controlled based upon ~~so that~~ a third crank angle G that generally is in the a midpoint between the first crank angle B and the second crank angle C. The third crank angle G becomes a specified target crank angle.

2720911  
062906